



## RTDs and Thermocouples Calibrator

CAL-400-3 / 4



Hand Held

CAL-402-3 / 4



Banch Mounted

<i>Hand Held (Portable)</i>		<i>Table Top</i>		
Display	4 ½ Digit LCD	3 ½ Digit LED	4 1/2Digit LCD	
Range	200 mV / 20 mA	200 mV/µA	2 V / mA	20 v / mA
Source	0 to 199.99 mV	0 to 199.9	0 to 1.999	0 to 19.99
Out put	0 to 19.999 mA	0 to 199.99	0 to 1.9999	0 to 19.999
Measure	0 to ±199.99 mV	0 to ±199.9	0 to ± 1.999	0 to ±19.99
Input	0 to ±19.999 mA	0 to ±199.99	0 to ± 1.9999	0 to ±19.999
Accuracy	0.05 % ± 2 Count	3 ½ Digit 0.1 % ± 2 count	4 ½ Digit 0.05% ± 2 count	
mA Load	500 E Max	1 K E Max		
Out Put	10 Turn POT Coarse & Fine			
Op. Temp.	0 to 50 °C ( RH <80%)			
Supply	9 V Dc battery x 2	230 V AC ± 10% 50 Hz 110 V AC ( Optional)		
Includes	Test Leads, Thermocouple Table & Traceable calibration certificate			