



RTDs Simulator (Calibrator)

CAL 404 / 405



Portable

CAL 403 / 406



Banch Mounted

Fix Range	: -100, -50, -25, 000 +25, 50, 150, 200, 250, 300, 400 ⁰ C for	
Out Put	CAL-404 / CAL-403	
12 Selectable	: -200 , -100, -50, 000, 50, 100, 150, 200, 300, 400, 500, 600 ⁰ C for CAL-405 / CAL-406	
Variable Range		: - 200 ⁰ C to 600 ⁰ C for CAL - 403, CAL - 406
Output		
Accuracy	: ± 0.1 % OHMS of FSR	
Compensation	: LWC (Long Wire Compensation) Of 100Meter sensor cable	
Include	: Test Leads, RTD Tables	
Option	: 12 Selectable Ranges as per your requirement is possible	
Operating	: 0 to 50 ⁰ C (RH < 80%)	
Supply	: Not required	
Box Size (HxWxD)	: Portable : 48 mm X 48 mm X 110 mm for CAL - 404 / CAL - 405 : Table Top : 88 mm X 210 mm X 230 mm for CAL - 403 / CAL - 406	

ORDERING CODE

CAL - XXX

XXX (BOX) RANGE

404		-100 to 400 ⁰ C
405	PORTABLE	-200 to 600 ⁰ C
403		-100 to 400 ⁰ C
406	TABLE TOP	-200 to 600 ⁰ C