



## Digital temperature Indicator ( Single & Multi channel)

**3 ½ & 4 ½ Digital Temperature Indicators & Multi Channel Indicators**



Display	3 ½ or 4 ½ Digit 7 Segment Red LED of 0.5" Ht.
Resolution	1°C (0.1°C Optional In Case Of Input Sensor RTD PT-100.)
Sensor Input	B, E, J, K, R, S, T TYPE T/C or RTD PT-100 mV, 4-20 mA I/P
Cold Junction Compensation	Atomic For T/C Input
Sensor Break Indication	By '1' at MSD
Indication Accuracy	J, K ± 1% , R, S ± 0.5 % , RTD ± 0.5 % , mV, mA ± 0.2 % ,
No of input sensor	1 For Single Channel Indicator , 6 / 12 For Multi Channel Indicators
Supply	230 V AC 50 Hz ( 110 V Ac Optional) ± 10%
Optional	Indication in °F Unit of Temp. Measurement , Reading Hold Facility

Dimensions (H x W x D )	96 x 96 x 120 mm	72 x 72 x 110 mm	48 x 48 x 120 mm
Panel Cutout (h x W)	92 x 92 mm	68 x 68 mm	46 x 92 mm

\* NB : Multi Channel indicators are available in 96 H x 96 W housing & Channel selection by Rotary Switch.

Salient Features:

High Stability and Reliability Sensor failed Protection